

Operating Specifications

Water Temp	35-95 deg (F)
Ambient Temp	35-120 deg (F) ambient temp
Feed Pressure	30-60 PSI dynamic (system should be regulated to 60 PSI static max for best performance)
Power	220V 60Hz 15 amp dedicated GFCI
TDS	< 3000 input
Max Output Pressure	65 PSI
Max Output Flow*	> 720 GPM
Recovery**	Up to 90% (inlet water temp & TDS dependent)

Pre-Filters (16)

(8) Shelco 12FOS4	12 x 20 um cartridges
(8) Filters – Stage 2	12 x 5 um cartridges

HANS Carbon Filters (24)

Carbon Cell	(144) 10" x 44" tanks in parallel with connecting manifold
Carbon Size	180 cu ft total
Media	Catalytic carbon

HANS Redundant Pumps (16)

Rated Flow	35 GPM at 50 PSI
Power	120-240v AC single phase

Anti-Scaling Injectors (8)

Pump	(8) Stenner ECON FP Series
Controller	(8) HANS Control Box

HANS Quad Reverse Osmosis (48)

Membrane Elements	(192) - 6" x 40" elements; 53,760 sq ft total active area
-------------------	--

Inlet Water Requirements

pH	5 to 9
TDS	< 3000 PPM
PFOA/PFOS	< PFOA (8000 PPT) < PSOS (16000 PPT)
Lead	< 150 PPB
Iron	< 6 PPM (Note - each ppm iron reduces grain capacity by 5)
Arsenic	< 50 PPB
Nitrate	< 30 PPM
Nitrite	< 3 PPM
Hardness	< 15 GPG
Chromium 6	< 300 PPB
Chromium Total	< 300 PPB
Barium	< 10 PPM
Radium	< 25 pCi/L
Fluoride	< 7.8 mg/L
Chlorine	< 4 PPM
Chloramine	< 4 PPM
VOCs (detailed list available)	–
Turbidity	1 NTU
Water Flow & Pressure	90-120 GPM @ 45 PSI min (inlet flow rates dependent on inlet TDS)

* > 720 GPM based on the following conditions: 77 deg F water temp; < 500 TDS; 50 PSI inlet; 35 PSI outlet


** Up to 90% recovery based on inlet TDS < 350

1,000,000 Gallons Per Day System

720 Gallons Per Minute
with Boost Pumps

(8) Shelco 20 um
Sediment Filters

(8) Shelco 5 um
Sediment Filters



(24) HANS
Carbon Filters
see page 14

(8) Anti-Scaling
Injectors

(16) HANS Redundant
Pumps
see page 26

(48) HANS
Quad RO Systems
see page 12

Footprint: 39 x 55 ft (12 x 16.8 meters)
2,145 sq ft (199.3 sq meters)

